

SPECIFICATION

Urea Solution “AUS-40”

A 40% high-purity marine-grade urea solution for marine SCR systems — manufactured and lab-tested in Australia to the values below, with full batch traceability.

Product specification	Monomark standard
1. Mass fraction of urea, %	39.5–40.5
2. Density at 20 °C, kg/m ³	1108.0–1116.0
3. Refractive index at 20 °C	1.3937–1.3954
4. Alkalinity as mass fraction of NH ₃ , %, max	0.3
5. Mass fraction of biuret, %, max	0.5
6. Mass concentration of aldehydes, mg/kg, max	6
7. Infusible particles, mg/kg, max	25
8. Mass concentration of phosphates, mg/kg, max	0.6
9. Mass concentration of aluminium, mg/kg, max	0.5
10. Mass concentration of calcium, mg/kg, max	0.5
11. Mass concentration of iron, mg/kg, max	0.5
12. Mass concentration of copper, mg/kg, max	0.3
13. Mass concentration of zinc, mg/kg, max	0.2
14. Mass concentration of chromium, mg/kg, max	0.3
15. Mass concentration of nickel, mg/kg, max	0.3
16. Mass concentration of magnesium, mg/kg, max	0.5
17. Mass concentration of sodium, mg/kg, max	0.5
18. Mass concentration of potassium, mg/kg, max	0.5

COMPANY DETAILS

Liquidia — Figure Eight Enterprises Pty Ltd
Head Office: Sydney, NSW, Australia
Distribution centres: Sydney · Brisbane · Perth · Melbourne
Australia-wide delivery

CONTACT

Phone: 1300 106 220
Email: orders@liquidia.com.au
Web: liquidia.com.au
Hours: Mon–Fri 9:00–18:30